Devor 30 P

Premium Subwoofer



Dual 12" horn loaded subwoofer

30Hz low frequency response

Sub cardioid dispersion

High SPL, low distortion

Mechanical force cancellation

Configuration	Active 2-way
Frequency response (±3dB)	30 Hz - 80 Hz
Max. SPL (cont./ peak)(calc.)	133 dB / 139 dB
Nominal dispersion	Sub-cardioid
Drivers	2×12"
Nominal impedance (front/rear)	8Ω / 8Ω
Power handling (cont./peak)	1000 W / 4000 W
Connections	2× Neutrik speakON 4-pole

Shallow depth form factor

Dimensions (WxHxD) mm

Weight

 $800 \times 800 \times 400$ mm 31.5 × 31.5 × 15.8 in 44,4 kg / 97.9 lb

Horn loading

The horn loading provides high sensitivity, good impulse response, and low distortion. The combination of high quality audio reproduction down to 30Hz, with very high SPL for the size and weight of the cabinet, makes the Devor 30 suitable for a range of applications.

Sub cardioid dispersion

The Devor 30 has a close to sub cardioid dispersion pattern all through its bandwidth – even at the lowest frequencies. This allows the sound pressure to be directed towards the audience, and reduces the need for acoustical treatment of

Mechanical force cancellation

Devor 30 is designed with dual 12" drivers, working mechanically in a push push configuration to feed the horn. This cancels out the movement exercised on the cabinet by each driver and minimizes distortion from the cabinet. This also contributes to the audience perceiving the bass signal through the air, along with rest of the music instead of out of time through the floor/ground.

High SPL, compact form factor

Devor 30 is appropriate for a broad range of applications. Its overall compact size, shallow depth, and small footprint

the room, as less energy is reflected off surrounding



make it practical for demanding applications where space is

critical. It is ideal for concert halls to clubs, cinemas, and

theaters, as well as a bass extension in studio, HiFi, and

home cinema setups.





Devor 30 P

Premium Subwoofer









